


COGS 300

Movement 02


Jan 15/26

①

Warm up: Fill a space with circles.




translation
linear
prismatic
rotational



Degree of freedom (DOF) = 1 motor

end effector



↑ working area
→ 11111
↑ axle

2-DOF working area?


(4)

How many dots in arm?

7

Robot : 6.

Grounded vs ungrounded.



↓
ambulating



Design a
pick + place
robot

• pick from
one side

• place on other side.


→ How does it navigate?

→ Error?

→ mitigation?
?


(5)

photo cell



⑥

Looks like



Works like



every DOF needs encoder
linear rotational



Reflection: What are the human body's encoders?

Rotational?


Linear?

Something else?


Movement 02

①

Warm up: Circles. fill area. faces?



circles because today we talk about mechanics. Two types of robot motion:





translation (prismatic) linear



rotation

but ...

These are interchangeable + composable:




Every motor is a "degree of freedom"


The end is an end effector
↳ "effects the world"

The working area of the robot is everywhere the robot can reach.

1-DOF rotational:



★ What is the shape of the working area with 2-DOF rot: (5)



2-link ex. \rightarrow circle.

★ How many dof for sphere? ~~★~~ Demo.

Not every config. equal. How many dof for arm? 7.

shoulder: 3

Elbow: 2

wrist: 2

\hookrightarrow no fingers.

Robot arm is 6 because of con't rotation.

★ How many for a 3D printer?

\hookrightarrow gantry robots or claw machine?

grounded vs ungrounded.

(4)

ambulating. vs. stationary.



you will make ambulating robots.
But some parts may be grounded.

★ Design pick + place robot.



delivery from
1 end of table
to other.

- How does it navigate?
- sources of error?
- mitigation?

★ Build photocell circuit.

The photocell is the basis of
a type of system called an optical
encoder. It is a "distance" sensor.

you know three types of sensors now:

photo cell



pot




switch



most systems use about this, more photo cell stands in for same kind of distance sensing. The problem is how to merge them.

A linear optical encoder has issues that we exaggerate here, but even high-precision systems have the same issue, just smaller.



kill your magical thinking!

★ redesign use distance sensing uses your sensors.